

255H



255H

TECHNICAL DATA

ENGINE

- MODEL ----- FPT CURSOR 9
- RATED POWER -----382.2HP (260KW) @ 2000RPM
- RATED SPEED ----- 2100RPM
- RATED TORQUE ----- 1,143FT-LB (1550NM) @1550RPM

SKYLINE

- CAPACITY-----2,400FT 1" SWAGED WIRE ROPE
- AVERAGE LINE PULL----- 56,000LBS(MAX DISP) 27,000LBS(MIN DISP)
- AVERAGE LINE SPEED-----313FPM(MIN DISP) 140FPM(MAX DISP)
- PUMP-----280CC/90GPM (586.7L/MIN)
- MOTOR-----SINGLE 160CC VDM

SKIDLIN

- CAPACITY-----2,400FT 3/4" OR 3,200FT 5/8" SWAGED WIRE ROPE
- AVERAGE LINE PULL----- 7,100LBS(MIN DISP) 36,000LBS(MAX DISP)
- AVERAGE LINE SPEED-----1,740FPM(MIN DISP) 315FPM(MAX DISP)
- PUMP----- CLOSED LOOP 210CC/116GPM (439.1L/MIN)
- MOTOR-----DUAL 270CC VDM

HAULBACK

- CAPACITY-----4,100FT 9/16" OR 3,200FT 5/8" SWAGED WIRE ROPE
- AVERAGE LINE PULL----- 5,800LBS(MIN DISP) 29,500LBS(MAX DISP)
- AVERAGE LINE SPEED-----2,150FPM(MIN DISP) 390FPM (MAX DISP)
- PUMP-----CLOSED LOOP 210CC/116GPM (283.9L/MIN)
- MOTOR-----DUAL 270CC VDM

HAYWIRE

- CAPACITY-----4,000FT 3/8" OR 5,600FT 5/16"
- AVERAGE LINE PULL----- 14,352LBS
- AVERAGE LINE SPEED-----670FPM
- MOTOR-----SINGLE 110CC FDM

HYDRAULIC YARDER


Designed for maximum control and efficiency in hydraulic yarding past 1,500ft.

Fully independent hydraulic winches allow for lines to be moved in any direction, at any speed, at any time.

Integrated three guyline system provides excellent stability while still being able to swing.

Easy, one piece move without a super haul permit, removing the cab or stripping lines.

INFO@SUMMITATTACHMENTS.COM
WWW.SUMMITATTACHMENTS.COM





255H